


Introduction to renumf90

UGA – 05/2016

Data File for blupf90 family:

- a) Only numbers – Integer or real
- a) All effects need to be renumbered from 1 consecutively



RENUMF90

**A renumbering program for the
BLUPF90 family of programs**

RENUMF90

- **Supports**
 - multiple traits
 - different effects per trait
 - alphanumeric and numeric fields
 - unknown parent groups
 - covariates for random regression models
- **Traces back pedigree for individuals in data file**
- **Performs comprehensive pedigree checking**
- **Provides data statistics**

RENUMF90 – Output files

- **Create files to be used by BLUPF90 family**
 - renf90.par - parameter file
 - renf90.dat - data recoded
 - renaddxx.ped - renumbered pedigree + statistics
 - renf90.tables - cross reference file with
renumbered and original effect

RENUMF90 – Input files

- Data file and pedigree file as flat files
 - Columns separated by at least one SPACE
 - No TABS !!!! (current version checks for it)
 - Input files cannot contain character #
 - Missing sire/dams must have code 0
 - code 00 is treated as a known animal
- Parameter file for renumf90
 - Has its own parameter file!!!!
 - Not the same for other programs!!!!

RENUMF90 parameter file

- Based on keywords in capital following by a line(s) with the corresponding data item
- Keywords need to be typed exactly
- Keywords need to occur in sequential order !!!
- Lines starting with # are treated as comments and are ignored

RENUMF90 parameter file

MANDATORY

Keyword	possible value	description
DATAFILE	character	The name of data file to be processed
TRAITS	integer	Position for observation (trait) in the data file
FIELDS_PASSED_TO_OUTPUT	integer	Position for the columns in the original data that will be passed to the renumbered data without changes Keep empty if not needed
WEIGHT(S)	integer	The position(s) for weight in the data file Keep empty if not needed
RESIDUAL_VARIANCE	real value(s)	Residual (co)variance
EFFECT	(next slide ...)	Description of an effect Repeatable

RENUMF90 parameter file

Effects

Keyword	Possible value	effect type	form
EFFECT	integer	cross	alpha
			numer
		cov	

Keyword (only for covariables)	Possible value	form
NESTED	integer	alpha
		numer

RENUMF90 parameter file

Creating interaction between effects

Keyword	possible value	description
COMBINE	integer	Should come before DATAFILE COMBINE 7 2 3 4 Columns 2, 3, 4 are combined into 7 They can be numer or alpha

RENUMF90 parameter file

Model: $y = \text{herd} + \text{sex} + \beta \text{ age} + e$

DATAFILE

data1.txt

TRAITS

FIELDS_PASSED_TO_OUTPUT

WEIGHT(S)

RESIDUAL_VARIANCE

EFFECT

ID	herd	sex	age	phen
ID006	A	1	1.0	3.0
ID009	A	2	1.0	2.0
ID012	A	1	2.0	4.0
ID007	B	2	2.0	6.0
ID010	B	1	1.0	3.0
ID013	B	2	2.0	6.0
ID008	C	1	2.0	6.0
ID011	C	2	1.0	6.0
ID014	C	1	1.0	8.0
ID015	C	2	2.0	4.0

RENUMF90 parameter file

Model: $y = \text{herd} + \text{sex} + \beta \text{ age} + e$

DATAFILE
data1.txt

TRAITS

5

FIELDS_PASSED_TO_OUTPUT

2

WEIGHT(S)

RESIDUAL_VARIANCE

1.0

EFFECT #1st effect

2 cross alpha

EFFECT #2nd effect

3 cross numer

EFFECT #3rd effect

4 cov

Fixed model

data1.txt

ID	herd	sex	age	phen
ID006	A	1	1.0	3.0
ID009	A	2	1.0	2.0
ID012	A	1	2.0	4.0
ID007	B	2	2.0	6.0
ID010	B	1	1.0	3.0
ID013	B	2	2.0	6.0
ID008	C	1	2.0	6.0
ID011	C	2	1.0	6.0
ID014	C	1	1.0	8.0
ID015	C	2	2.0	4.0

RENUMF90 parameter file

Random Effects

Keyword after EFFECT	possible value	description
RANDOM	diagonal	Non-correlated
	animal	Correlation structure among animals
	sire	Not implemented yet

Keyword	possible value	description
OPTIONAL	pe	Permanent environmental
	mat	Maternal
	mpe	Permanent environmental maternal (only if mat is used)

RENUMF90 parameter file

Random effects file section

Keyword after RANDOM (animal or sire only)	possible value	description
FILE	character	Name of the pedigree file for animal or sire models only

Keyword after FILE (for RANDOM animal and sire only)	possible value	description
FILE_POS	integer	Specifies positions in the pedigree for ani sire dam alternate_dam yob Default: 1 2 3 0 0 If maternal effect alternate_dam

Keyword (for RANDOM animal and sire only)	possible value	description
SNP_FILE	character	Optional: If genomic info is to be used Name of the SNP file Format: ID 011122211155152222

RENUMF90 parameter file

Pedigree options

Keyword (for RANDOM animal and sire only)	possible value	description
PED_DEPTH	Integer	Optional Specifies the depth of pedigree search Default = 3 All pedigree = 0

Keyword (for RANDOM animal and sire only)	possible value	description
GEN_INT	Integer min avg max	Optional Specifies min, avg, max generation interval; if yob is present Average used to predict yob of

Keyword (for RANDOM animal and sire only)	possible value	description
REC_SEX	Integer	Optional Specifies which parent has records Checks if records are found in specific sex

RENUMF90 parameter file

Unknown Parent Group options

Keyword (for RANDOM animal and sire only)	possible value	description
UPG_TYPE	yob 1990 1992 ... in_pedigrees internal	Optional UPG assigned based on yob Missing parent receives -x x is the UPG number UPG assigned by a user-written function (not implemented yet)

RENUMF90 parameter file

Inbreeding option

Keyword (for RANDOM animal and sire only)	possible value	description
INBREEDING	pedigree	Optional Calculates inbreeding and saves in the renumbered pedigree file
	file	Reads inbreeding from an external file format: original_ID inbreeding (0 to 1)

RENUMF90 parameter file

Random Regression options

Keyword	possible value	description
RANDOM_REGRESSION		Specifies that random regression should be applied to the random effects
	data	If covariables are in the data
	legendre	Generates legendre polynomials (not implemented yet)

Keyword	possible value	description
RR_POSITON	Integer	Specifies positions of covariables if RANDOM_REGRESSION type is data

RENUMF90 parameter file

(CO)VARIANCES for Random effects

Keyword	possible value	description
(CO)VARIANCES	real	(co)variance for the animal effect dimension should account for number of traits and random correlated effects

DIRECT	32.79	-7.22	-11.07	-8.59	-0.35	-0.68
	-7.22	258.06	87.66	4.55	21.57	29.92
	-11.07	87.66	194.34	4.54	23.12	26.67
COV DIRECT,MAT	-8.59	4.55	4.54	46.91	0.6	-0.08
	-0.35	21.57	23.12	0.6	132.24	29.95
	-0.68	29.92	26.67	-0.08	29.95	132.65

MATERNAL

RENUMF90 parameter file

(CO)VARIANCES structure

- 3 trait (T1-T3) and 2 correlated effects (E1-E2)

		E1			E2		
		T1	T2	T3	T1	T2	T3
E1	T1						
	T2						
	T3						
E2	T1						
	T2						
	T3						

RENUMF90 parameter file

(CO)VARIANCES for Random effects

Keyword	possible value	description
(CO)VARIANCES	real	(co)variance for non-correlated random effects

Keyword	possible value	description
(CO)VARIANCES_PE	real	(co)variance for the PE effect if present

Keyword	possible value	description
(CO)VARIANCES_MPE	real	(co)variance for the MPE effect if present

RENUMF90 parameter file

Keyword	optional	possible values
COMBINE	optional	definition of new field as a combination of existing fields
DATAFILE	mandatory	name of raw data file
TRAITS	mandatory	positions of observations in the raw data file
FIELDS_PASSED	mandatory	positions of items in the raw data file to be passed to renf90.dat
WEIGHT(S)	mandatory	positions of weights in the raw data file
RESIDUAL_VARIANCE	mandatory	residual covariance matrix
EFFECT	mandatory	effect description
NESTED	optional	positions of nested covariates
RANDOM	optional	declaration of random effect
OPTIONAL	optional	declaration of MAT, PE, MPE
FILE	optional	name of raw pedigree file
FILE_POS	optional	positions of animal ID, sire ID and dam ID
SNP_FILE	optional	name of SNP marker file
PED_DEPTH	optional	the maximum generation back from animals with phenotype or genotype
GEN_INT	optional	generation interval to set unknown parent groups (UPG)
REC_SEX	optional	check if records are found in specific sex
UPG_TYPE	optional	UPG specification
INBREEDING	optional	create pedigree file with inbreeding
RANDOM_REGRESSION	optional	put covariates for random regressions
RR_POSITION	optional	positions of covariates for random regressions
(CO)VARIANCES	optional	covariance components
(CO)VARIANCES_PE	optional	covariance components for animal's PE effects
(CO)VARIANCES_MPE	optional	covariance components for maternal PE effects
OPTION	optional	option parameters

RENUMF90 parameter file

Options passed to blupf90

- All lines that begin with keyword OPTION are passed to parameter file renf90.par
- This allows automatization of process by using scripts
- For example:
 - OPTION sol se

RENUMF90 parameter file

Extra options

The following options can be added at the end of the parameter file to redefine parameters used to read the input file:

- the default size of character fields

```
OPTION alpha_size nn
```

where *nn* is the new size.

- the size of the record length

```
OPTION max_string_readline nn
```

where *nn* is the new size.

- the maximum number of fields

```
OPTION max_field_readline nn
```

where *nn* is the number of fields.

RENUMF90 parameter file

Hints

- Keyword EFFECT is repeated as many time as effects in the model
- If (CO)VARIANCES for any effect are missing, default matrix with 1.0 in diagonal and 0.1 on off-diagonal will be used
 - WARNING: for EM-REML convergence rate is improved if starting values are too large rather than too small !!!

RENUMF90 parameter file

Model: $y = \text{herd} + \text{sex} + \beta \text{ age} + e$

```
DATAFILE  
data1.txt  
TRAITS  
5  
FIELDS_PASSED_TO_OUTPUT  
2  
WEIGHT(S)  
  
RESIDUAL_VARIANCE  
1.0  
EFFECT      #1st effect  
2 cross alpha  
EFFECT      #2nd effect  
3 cross numer  
RANDOM  
diagonal  
(CO)VARIANCES  
0.5  
EFFECT      #3rd effect  
4 cov
```

What if we want to consider sex as random?

data1.txt

ID	herd	sex	age	phen
ID006	A	1	1.0	3.0
ID009	A	2	1.0	2.0
ID012	A	1	2.0	4.0
ID007	B	2	2.0	6.0
ID010	B	1	1.0	3.0
ID013	B	2	2.0	6.0
ID008	C	1	2.0	6.0
ID011	C	2	1.0	6.0
ID014	C	1	1.0	8.0
ID015	C	2	2.0	4.0

RENUMF90 parameter file

Model: $y = \text{herd} + \text{sex} + \text{animal} + \beta \text{ age} + e$

```
DATAFILE  
data1.txt  
TRAITS  
5  
FIELDS_PASSED_TO_OUTPUT  
2  
WEIGHT(S)  
  
RESIDUAL_VARIANCE  
1.0  
EFFECT #1st effect  
2 cross alpha  
EFFECT #2nd effect  
3 cross numer  
EFFECT #3rd effect  
4 cov  
EFFECT #4th effect  
1 cross alpha  
RANDOM  
animal  
FILE  
ped1.txt  
FILE_POS  
1 2 3 0 0  
(CO)VARIANCES  
0.5
```

What if we want to consider animal effect as random?

ped1.txt

ID	Sire	Dam
ID006	ID001	ID003
ID009	ID001	ID004
ID012	ID001	ID005
ID007	ID001	ID003
ID010	ID001	ID004
ID013	ID002	ID005
ID008	ID002	ID003
ID011	ID002	ID004
ID014	ID002	ID005
ID015	ID002	ID003

data1.txt

ID	herd	sex	age	phen
ID006	A	1	1.0	3.0
ID009	A	2	1.0	2.0
ID012	A	1	2.0	4.0
ID007	B	2	2.0	6.0
ID010	B	1	1.0	3.0
ID013	B	2	2.0	6.0
ID008	C	1	2.0	6.0
ID011	C	2	1.0	6.0
ID014	C	1	1.0	8.0
ID015	C	2	2.0	4.0

RENUMF90 output files

Pedigree file: renaddxx.ped

Data file: renf90.dat

Parameter file: renf90.par

Renumbering table: renf90.table

RENUMF90 output files

Pedigree file: renaddxx.ped

- Structure:
 1. Animal ID (from 1)
 2. Parent 1 ID or UPG number for parent 1
 3. Parent 2 ID or UPG number for parent 2
 4. 3 minus number of known parents
 5. Known or estimated year of birth (0 if not provided)
 6. Number of known parents, if animal has genotype:
10+number of known parents
 7. Number of records
 8. Number of progeny as parent 1
 9. Number of progeny as parent 2
 10. Original animal ID

RENUMF90 output files

Pedigree file: renaddxx.ped

- If option for inbreeding is used:

Column 4:

$$\text{inb/upg code} = 4000 / [(1+ms)(1-Fs) + (1+md)(1-Fd)]$$

ms (md) is 0 if sire (dam) is known, and 1 otherwise

Fs (Fd) is the coefficient of inbreeding of sire (dam)

Ex: inb/upg code for the animal with both parents F=0

RENUMF90 output files

renumbering tables: renf90.tables

- For each cross-classified effects
 - Original ID, count, consecutive number
- Useful
 - To translate solutions from BLUPF90 program into original alphanumeric values
 - Check counts of records by level

```
DATAFILE
data.test
TRAITS
3 4
FIELDS_PASSED_TO_OUTPUT
2 1 # passing alphanumeric
WEIGHT(S)

RESIDUAL_VARIANCE
5 2
2 4

EFFECT
1 1 cross alpha
EFFECT
2 2 cross alpha
RANDOM
animal
OPTIONAL
mat mpe pe
FILE
test.ped
(CO)VARIANCES
10 3 2 1
3 11 4 5
2 4 12 6
1 5 6 13.01
(CO)VARIANCES_PE
5.3 2.1
2.1 4.85
(CO)VARIANCES_MPE
1.03 .27
.27 .85
EFFECT
5 0 cov
NESTED
1 0 alpha
EFFECT
6 6 cross alpha
RANDOM
diagonal
```

Example of RENUMF90 parameter file

data file - data.test

```
1 aa 34.5 11 12 zz
3 bb 21.333 22 23 xx
8 cc 23.666 33 34 yy
1 dd 29 44 45 xx
3 aa 30 55 56 yy
5 bb 1234567.890 66 67 zz
```

pedigree file - test.ped

```
qq 0 0
aa 0 0
bb qq aa
cc qq 0
dd 0 aa
```

RENUMF90 output files

data file - renf90.dat

```
34.5 11 1 3 5 12 1 3 aa 1
21.333 22 2 1 3 23 2 1 bb 3
23.666 33 4 4 7 34 4 2 cc 8
29 44 1 2 3 45 1 1 dd 1
30 55 2 3 5 56 2 2 aa 3
1234567.890 66 3 1 3 67 3 3 bb 5
```

renumbering tables - renf90.tables

```
Effect group 1 of column 1 with 4 levels
Value # consecutive number
```

```
1 2 1
3 2 2
5 1 3
8 1 4
```

```
Effect group 3 of column 1 with 4 levels
Value # consecutive number
```

```
1 2 1
3 2 2
5 1 3
8 1 4
```

```
Effect group 4 of column 1 with 3 levels
Value # consecutive number
```

```
xx 2 1
yy 2 2
```

Pedigree file - renadd02.ped

```
1 6 3 1 0 2 2 0 0 bb
6 0 0 1 0 0 0 2 0 qq
2 0 3 1 0 1 1 0 0 dd
7 0 0 1 0 0 0 0 1 D@00000002
5 0 0 1 0 0 0 0 1 D@00000001
3 0 5 1 0 1 2 0 2 aa
4 6 7 1 0 2 1 0 0 cc
```

parameter file - testpar1

```
# Parameter file for program renf90; it is translated to parameter
# file for BLUPF90 family programs.
DATAFILE
data.test
TRAITS
3 4
FIELDS_PASSED_TO_OUTPUT
2 1 # passing alphanumeric
WEIGHT(S)

RESIDUAL_VARIANCE
5 2
2 4
EFFECT
1 1 cross alpha
EFFECT
2 2 cross alpha
RANDOM
animal
OPTIONAL
mat mpe pe
FILE
test.ped
(CO)VARIANCES
10 3 2 1
3 11 4 5
2 4 12 6
1 5 6 13.01
(CO)VARIANCES_PE
5.3 2.1
2.1 4.85
(CO)VARIANCES_MPE
1.03 .27
.27 .85
EFFECT
5 0 cov
NESTED
1 0 alpha
EFFECT
6 6 cross alpha
RANDOM
diagonal
```

new parameter file - renf90.par

```
# BLUPF90 parameter file created by RENF90
DATAFILE
renf90.dat
NUMBER_OF_TRAITS
2
NUMBER_OF_EFFECTS
7
OBSERVATION(S)
1 2
WEIGHT(S)

EFFECTS: POSITIONS_IN_DATAFILE NUMBER_OF_LEVELS TYPE_OF_EFFECT[EFFECT NESTED]
3 3      4 cross
4 4      7 cross
5 5      7 cross
5 5      7 cross
4 4      7 cross
6 0      4 cov 7 0
8 8      3 cross
RANDOM_RESIDUAL_VALUES
5.000    2.000
2.000    4.000
RANDOM_GROUP
2 3
RANDOM_TYPE
add_animal
FILE
renadd02.ped
(CO)VARIANCES
10.00    3.000    2.000    1.000
3.000    11.00    4.000    5.000
2.000    4.000    12.00    6.000
1.000    5.000    6.000    13.01
RANDOM_GROUP
4
RANDOM_TYPE
diagonal
FILE

(CO)VARIANCES
1.030    0.2700
0.2700   0.8500
RANDOM_GROUP
5
RANDOM_TYPE
diagonal
FILE

(CO)VARIANCES
5.300    2.100
2.100    4.850
RANDOM_GROUP
7
RANDOM_TYPE
diagonal
FILE

(CO)VARIANCES
1.000    0.1000
0.1000   1.000
```

renumf90 FAQ

- 1) renumf90 cannot find the data file Check for typos
- 2) How to include quadratic covariate? Column in data file
- 3) Error when trying to use covariate 2 cov numer
- 4) I want to have original IDs in renf90.dat FIELDS_PASSED_TO_OUTPUT
- 5) Fixed effects in renf90.dat are different from original renf90.tables
- 6) Why solutions are not with original ID? ask Ignacy Misztal
- 7) How to match solutions with original ID? Bash scripting

For trait 1 when animal is
effect number 2

```
$awk '{ if ($1==1 && $2==2) print $3,$4}' solutions | sort +0 -1 > sol.temp  
$awk '{print $1,$10}' renadd02.ped | sort +0 -1 > ids.temp  
$join -1 +1 -2 +1 ids.temp sol.temp > renumbered_original_EBV
```

renumf90 FAQ

8) When to run renumf90?

a) Objective to compare models

Run renumf90 ONCE with the most complete model

Remove effects from renf90.par

b) Objective to mask phenotypes for some animals for validation

Run renumf90 ONCE with the complete data

Remove animals from renf90.dat

c) Objective to compare non-genomic vs genomic model

Run renumf90 ONCE with SNP file

For non-genomic: Remove option for SNP file from renf90.par

blupf90 family

renf90.par

RANDOM_TYPE
add_animal

Type of random effect (distribution)
[diagonal](#), [add_sire](#), [add_an_upg](#), [add_an_upginb](#), [par_domin](#), or [user_file](#)

new parameter file - renf90.par

```
# BLUPF90 parameter file created by RENF90
DATAFILE
  renf90.dat
NUMBER_OF_TRAITS
  2
NUMBER_OF_EFFECTS
  7
OBSERVATION(S)
  1 2
WEIGHT(S)

EFFECTS: POSITIONS_IN_DATAFILE NUMBER_OF_LEVELS TYPE_OF_EFFECT[EFFECT NESTED]
  3 3      4 cross
  4 4      7 cross
  5 5      7 cross
  5 5      7 cross
  4 4      7 cross
  6 0      4 cov  7  0
  8 8      3 cross
RANDOM_RESIDUAL_VALUES
  5.000    2.000
  2.000    4.000
RANDOM_GROUP
  2 3
RANDOM_TYPE
  add_animal
FILE
rennadd02.ped
(CO)VARIANCES
  10.00    3.000    2.000    1.000
  3.000    11.00    4.000    5.000
  2.000    4.000    12.00    6.000
  1.000    5.000    6.000    13.01
RANDOM_GROUP
  4
RANDOM_TYPE
  diagonal
FILE

(CO)VARIANCES
  1.030    0.2700
  0.2700   0.8500
RANDOM_GROUP
  5
RANDOM_TYPE
  diagonal
FILE

(CO)VARIANCES
  5.300    2.100
  2.100    4.850
RANDOM_GROUP
  7
RANDOM_TYPE
  diagonal
FILE

(CO)VARIANCES
  1.000    0.1000
  0.1000   1.000
```

blupf90 family

renf90.par

- *user_file*
 - a matrix is read from file
 - Matrix is stored only upper- or lower-triangular
 - Matrix file:
 - row, col, value
- *user_file_i*
 - As before but the matrix will be inverted
- *par_domin*
 - A parental dominance file created by program RENDOM

Options for blupf90

```
OPTION conv_crit 1e-12
```

Set convergence criteria (default 1e-12).

```
OPTION maxrounds 10000
```

Set maximum number of rounds (default 1000).

```
OPTION solv_method FSPAK
```

Select solutions by FSPAK, SOR or PCG (default PCG).

```
OPTION r_factor 1.6
```

Set relaxation factor for SOR (default 1.4).

```
OPTION sol se
```

Store solutions and s.e.

Options for blupf90

Missing data
Not pedigree!



```
OPTION missing -999
```

Specify missing observations (default 0).

```
OPTION residual
```

y-hat and residual will be included in "yhat_residual".

```
OPTION blksize 3
```

Set block size for preconditioner (default 1).

```
OPTION SNP_file.snp
```

Specify the SNP file name to use genotype data.

Options for airemlf90

```
OPTION conv_crit 1d-12
```

Convergence criterion (default 1d-10).

```
OPTION maxrounds 1000
```

Maximum rounds (default 5000). When the number = 0, the program calculates BLUP without iterating REML

```
OPTION EM-REML 10
```

Run EM-REML (REMLF90) for first 10 rounds to get initial variances within the parameter space (default 0).

```
OPTION use_yams
```

Run the program with YAMS (modified FSPAK). The computing time can be dramatically improved.

```
OPTION se_covar_function <label> <function>
```

Options for airemlf90

Heterogeneous residual variances for a single trait

```
OPTION hetres_pos 10 11
```

Specify the position of covariables.

```
OPTION hetres_pol 4.0 0.1 0.1
```

Initial values of coefficients for heterogeneous residual variances using $\ln(a_0, a_1, a_2, \dots)$ to make these values.

Heterogeneous residual variances for multiple traits

Convergence will be very slow with multiple trait heterogeneous residual variances

```
OPTION hetres_pos 10 10 11 11
```

or

```
OPTION hetres_pos 10 11 12 13
```

Specify the position of covariables (trait first). "10 10" or "10 11" could be linear for first and second traits.
"11 11" or "12 13" could be quadratic.

```
OPTION hetres_pol 4.0 4.0 0.1 0.1 0.01 0.01
```

Initial values of coefficients for heterogeneous residual variances using $\ln(a_0, a_1, a_2, \dots)$ to make these values (trait first).
"4.0 4.0" are intercept for first and second traits.
"0.1 0.1" could be linear and "0.01 0.01" could be quadratic.
To transform back to the original scale, use $\exp(a_0 + a_1 * X_1 + a_2 * X_2)$.

Common problems for blupf90 family

- Wrong data file and pedigree name
 - Program does not stop if wrong file name not exist
 - Check outputs for data file name and number of records and pedigree read

```
round = 4995 convergence =      NaN
round = 4996 convergence =      NaN
round = 4997 convergence =      NaN
round = 4998 convergence =      NaN
round = 4999 convergence =      NaN
round = 5000 convergence =      NaN
  5001 iterations,  convergence criterion=      NaN
solutions stored in file: "solutions"
```

Common problems for blupf90 family

- Wrong position or formats for observation and effects
- Misspelling of Keywords
 - Program may stop
- (Co)variance matrices not symmetric, not positive definite
 - Program may not stop
- Large numbers (e.g. 305-day milk yield 10,000 kg)
 - Scale down i.e. $10,000 / 1,000 = 10$

General output form blupf90 family

name of parameter file?

exmr99s

BLUPF90 1.46

Check file names

Parameter file:

exmr99s

Data file:

renco99s

Number of Traits

3

Number of Effects

3

Position of Observations

3 4 5

Position of Weight (1)

0

Value of Missing Trait/Observation

0

Check model

EFFECTS

#	type	position (2)	levels	[positions for nested]	
1	cross-classified	1 1 1			51
2	cross-classified	2 2 2			2147
3	cross-classified	2 2 2			2699

General output form blupf90 family

Residual (co)variance Matrix

1825.3	909.82	842.39
909.82	2057.0	1309.8
842.39	1309.8	1716.4

Random Effect(s) 2

Type of Random Effect: diagonal
trait effect (CO)VARIANCES

1	2	2523.	1901.	1885.
2	2	1901.	1965.	1809.
3	2	1885.	1809.	1926.

Check (co)variances

Random Effect(s) 3

Type of Random Effect: additive animal with unknown parent groups
Pedigree File: renpe99s

trait effect (CO)VARIANCES

1	3	613.7	-360.9	80.93
2	3	-360.9	475.2	319.5
3	3	80.93	319.5	666.6

REMARKS

- (1) Weight position 0 means no weights utilized
- (2) Effect positions of 0 for some effects and traits means that such effects are missing for specified traits

Data record length =

5

equations = 14691

G

2522.6	1901.4	1885.4
1901.4	1965.3	1808.9
1885.4	1808.9	1925.9

G

613.75	-360.90	80.927
-360.90	475.23	319.52
80.927	319.52	666.60

hash matrix increased from 131072 to 262144 % filled: 0.8000
read 4539 records in 0.1445990 s, 127095 nonzeros
read 2697 additive pedigrees
finished peds in 0.2006180 s, 191175 nonzeros

Check maximum number of columns to read

Check number of records And pedigree read

General output form blupf90 family

- Output printed on the screen is not saved in any file!
- Should use redirection or pipes to store output

renumf90

```
echo renf90.par | renumf90 | tee renf.log
```

blupf90

```
echo renf90.par | blupf90 | tee blup.log
```

airemlf90

```
echo renf90.par | remlf90 | tee aireml.log
```

Run in background + Save output

```
$vi ai.sh  
#type the following commands inside ai.sh  
    blupf90 <<AA > blup.log  
    renf90.par  
    AA  
#save and exit  
$sh ai.sh & #can replace sh by bash
```

```
$vi gibbs.sh  
#type the following commands inside ai.sh  
    gibbs2f90 <<AA > gibbs.log  
    renf90.par  
    1000 0  
    10  
    AA  
#save and exit  
$sh gibbs.sh & #can replace sh by bash
```